



型式	T1	T2	A (mm)	B (mm)
KB-0613	1/2"	1/8"	22.0	23.5
KB-0813	1/2"	1/4"	22.0	23.0
KB-0820	3/4"	1/4"	29.0	25.0
KB-0825	1"	1/4"	35.5	27.0
KB-1013	1/2"	3/8"	22.0	23.5
KB-1020	3/4"	3/8"	29.0	25.0
KB-1320	3/4"	1/2"	29.0	25.0
KB-1325	1"	1/2"	35.5	27.0
KB-1330	1.1/4"	1/2"	43.5	31.5
KB-1340	1.1/2"	1/2"	50.0	33.5
KB-1350	2"	1/2"	61.5	38.0
KB-2025	1"	3/4"	35.5	27.0
KB-2030	1.1/4"	3/4"	43.5	31.5
KB-2040	1.1/2"	3/4"	50.5	33.0
KB-2050	2"	3/4"	61.5	38.0
KB-2530	1.1/4"	1"	43.5	31.2
KB-2540	1.1/2"	1"	50.5	33.5
KB-2550	2"	1"	61.5	38.0
KB-3040	1.1/2"	1.1/4"	50.5	33.0
KB-3050	2"	1.1/4"	61.0	38.0
KB-3063	2.1/2"	1.1/4"	79.0	42.0
KB-4050	2"	1.1/2"	61.0	38.0
KB-4063	2.1/2"	1.1/2"	78.5	42.0
KB-4075	3"	1.1/2"	92.0	45.0
KB-5063	2.1/2"	2"	78.5	42.0
KB-5075	3"	2"	92.0	45.0
KB-6375	3"	2.1/2"	92.0	45.0

□T1 (BSPTメネジ) × T2 (BSPTメネジ)

■ 材質

本体 : ポリアミド (ガラス繊維強化ナイロン6)

名称	樹脂製ブッシング
型式	KB-XXXX
株式会社 イリテック・プラス	