



型式	T1	T2	A (mm)	B (mm)	C (mm)
KS-1320	3/4"	1/2"	34.0	28.0	42.5
KS-1325	1"	1/2"	41.5	28.0	47.5
KS-2025	1"	3/4"	41.5	34.0	45.5
KS-2030	1.1/4"	3/4"	51.5	34.0	52.0
KS-2040	1.1/2"	3/4"	58.5	34.0	52.0
KS-2050	2"	3/4"	71.5	34.5	60.5
KS-2530	1.1/4"	1"	51.0	41.5	49.0
KS-2540	1.1/2"	1"	58.0	41.0	51.5
KS-2550	2"	1"	71.5	41.0	59.5
KS-3040	1.1/2"	1.1/4"	58.0	51.0	53.0
KS-3050	2"	1.1/4"	71.5	51.0	61.5
KS-4050	2"	1.1/2"	71.5	58.0	58.0
KS-4063	2.1/2"	1.1/2"	92.5	59.0	70.0
KS-5063	2.1/2"	2"	92.5	72.5	69.0
KS-5075	3"	2"	110.0	72.5	78.5
KS-6375	3"	2.1/2"	110.0	92.5	73.0

□T1 (BSPTメス寸) × T2 (BSPTメス寸)

■ 材質

本体 : ポリアミド (ガラス繊維強化ナイロン6)

名称	樹脂製異径ソケット
型式	KS-XXXX
株式会社 イリテック・プラス	