



型式	T1	T2	A±0.5(mm)	B±0.5(mm)
KB-0615	1/8"	1/2"	22.0	23.5
KB-0815	1/4"	1/2"	22.0	23.0
KB-0820	1/4"	3/4"	29.0	25.0
KB-0825	1/4"	1"	35.5	27.0
KB-1015	3/8"	1/2"	22.0	23.5
KB-1020	3/8"	3/4"	29.0	25.0
KB-1520	1/2"	3/4"	29.0	25.0
KB-1525	1/2"	1"	35.5	27.0
KB-1532	1/2"	1.1/4"	43.5	31.5
KB-1540	1/2"	1.1/2"	50.0	33.5
KB-1550	1/2"	2"	61.5	38.0
KB-2025	3/4"	1"	35.5	27.0
KB-2032	3/4"	1.1/4"	43.5	31.5
KB-2040	3/4"	1.1/2"	50.5	33.0
KB-2050	3/4"	2"	61.5	38.0
KB-2532	1"	1.1/4"	43.5	31.2
KB-2540	1"	1.1/2"	50.5	33.5
KB-2550	1"	2"	61.5	38.0
KB-3240	1.1/4"	1.1/2"	50.5	33.0
KB-3250	1.1/4"	2"	61.0	38.0
KB-3265	1.1/4"	2.1/2"	79.0	42.0
KB-4050	1.1/2"	2"	61.0	38.0
KB-4065	1.1/2"	2.1/2"	79.0	42.0
KB-4080	1.1/2"	3"	92.0	45.0
KB-5065	2"	2.1/2"	78.5	42.0
KB-5080	2"	3"	92.0	45.0
KB-6580	2.1/2"	3"	92.0	45.0

□ T1 (BSPTメスネジ) × T2 (BSPTオスネジ)

■ 材質

本体 : ポリアミド(ガラス繊維強化ナイロン6)

■ 耐圧

: 1/8"~2" 20°C 1.6MPa

: 2.1/2" 20°C 1.2MPa

: 3" 20°C 1.0MPa

名称	樹脂製ブッシング
型式	KB-XXXX
株式会社イリテック・プラス	