



型式	T1	T2	A±0.5 (mm)	B±0.5 (mm)
KN-0608	1/8"	1/4"	14.0	31.0
KN-0610	1/8"	3/8"	18.0	33.0
KN-0615	1/8"	1/2"	22.5	37.3
KN-0810	1/4"	3/8"	18.5	34.5
KN-0815	1/4"	1/2"	22.5	39.0
KN-1015	3/8"	1/2"	26.0	50.5
KN-1020	3/8"	3/4"	31.0	55.5
KN-1520	1/2"	3/4"	28.5	48.0
KN-1525	1/2"	1"	35.0	51.5
KN-2025	3/4"	1"	35.5	54.0
KN-2032	3/4"	1.1/4"	45.0	66.0
KN-2040	3/4"	1.1/2"	51.5	68.0
KN-2050	3/4"	2"	63.5	73.0
KN-2532	1"	1.1/4"	44.0	60.0
KN-2540	1"	1.1/2"	50.0	64.5
KN-2550	1"	2"	63.0	74.0
KN-3240	1.1/4"	1.1/2"	50.0	62.0
KN-3250	1.1/4"	2"	63.0	73.0
KN-3265	1.1/4"	2.1/2"	79.0	79.5
KN-4050	1.1/2"	2"	62.5	70.0
KN-4065	1.1/2"	2.1/2"	79.0	77.0
KN-4080	1.1/2"	3"	91.5	86.0
KN-5065	2"	2.1/2"	79.0	78.0
KN-5080	2"	3"	91.5	86.0
KN-6580	2.1/2"	3"	92.0	85.0

□T1 (BSPTオスネジ) × T2 (BSPTオスネジ)

■材質

本体 : ポリアミド(ガラス繊維強化ナイロン6)

■耐圧

: 1/8"~2" 20°C 1.6MPa

: 2.1/2" 20°C 1.2MPa

: 3" 20°C 1.0MPa

名称	樹脂製異径ニップル
型式	KN-XXXX
株式会社イリテック・プラス	